



WebLog 250

Art.No.: WEBLOG250

- ⊙ M-Bus data logger for 250 meters
- ⊙ 7" LED Touchscreen
- ⊙ Remote readout via web browser
- ⊙ USB, Ethernet, W-LAN, RS232C, Modem (analogue/GPRS)
- ⊙ Data export as XML, XLSX, CSV via E-Mail, FTP, USB

- ✱ 86 x 234 x 264 mm
- ✱ 800 x 480 Pixel Touchscreen
- ✱ Wall mounted or DIN rail TS35
- ✱ integrated power supply (110 - 250 V)
- ✱ 1 GB memory



Central Unit 250 / 120

Art.No.: DR001 / DR001

- ⊙ M-Bus data logger for 250 or 120 slaves
- ⊙ Operation on-site by keyboard and LCD
- ⊙ Export of measured data to PC database
- ⊙ Service and modem interface

- ✱ 85 x 200 x 240 mm
- ✱ Wall mounted
- ✱ RS232C
- ✱ external Modem (e.g. MOD001)
- ✱ plug-in, wall mounted or DIN rail power supply (scope of delivery)
- ✱ 256kB memory



W60 Data Logger

Art.No.: MR004DL

- ⊙ M-Bus data logger for 60 slaves
- ⊙ Level converter for 60 slaves
- ⊙ Operation on-site by keyboard and LCD
- ⊙ Integrated power supply

- ✱ 71 x 165 x 175 mm
- ✱ Wall mounted
- ✱ RS232C and RS485
- ✱ external modem (e.g. MOD001)
- ✱ 230V or 110V power supply selectable
- ✱ 512kB memory



W60 Remote Display

Art.No.: MR004FA

- ⊙ M-Bus remote display for 60 slaves
- ⊙ Level converter for 60 slaves
- ⊙ Operation on-site by keyboard and LCD
- ⊙ Integrated power supply

- ✱ 71 x 165 x 175 mm
- ✱ Wall mounted
- ✱ RS232C and RS485
- ✱ external modem (e.g. MOD001)
- ✱ 230V or 110V power supply selectable



C20 Data Logger

Art.No.: MR006DL

- ⊙ M-Bus Data logger for 20 slaves
- ⊙ Level converter for 20 slaves
- ⊙ Operation on-site by keyboard and LCD
- ⊙ Rail mounted

- ✱ 58 x 106 x 96 mm
- ✱ Mounted on DIN rail TS35
- ✱ RS232C
- ✱ external modem (e.g. MOD001)
- ✱ external power supply 12 .. 24 V (not in scope of delivery)
- ✱ 1MB memory optional 2MB/4MB



C20 Remote Display

Art.No.: MR006FA

- ⊙ M-Bus remote display for 20 slaves
- ⊙ Level converter for 20 slaves
- ⊙ Operation on-site by keyboard and LCD
- ⊙ Rail mounted

- ✱ 58 x 106 x 96 mm
- ✱ Mounted on DIN rail TS35
- ✱ RS232C
- ✱ external modem
- ✱ external power supply 12 .. 24 V (not in scope of delivery)



C3 Data Logger

Art.No.: MR005DL

- ⊙ M-Bus Data logger for 3 slaves
- ⊙ Level converter for 3 slaves
- ⊙ Operation on-site by keyboard and LCD
- ⊙ Rail mounted

- ✱ 558 x 106 x 96 mm
- ✱ Mounted on DIN rail TS35
- ✱ RS232C
- ✱ external modem (e.g. MOD001)
- ✱ external power supply 12 .. 24 V (not in scope of delivery)
- ✱ 1MB memory optional 2MB/4MB



C3 Remote Display

Art.No.: MR005FA

- ⊙ M-Bus remote display for 3 slaves
- ⊙ Level converter for 3 slaves
- ⊙ Operation on-site by keyboard and LCD
- ⊙ Rail mounted

- ✱ 58 x 106 x 96 mm
- ✱ Mounted on DIN rail TS35
- ✱ RS232C
- ✱ external modem
- ✱ external 24V power supply (not in scope of delivery)



M-Bus Level Converter

Art.No.: PW250

- ⊙ M-Bus converter for up to 250 slaves
- ⊙ Repeater for M-Bus extension: up to 250 slaves or cable network
- ⊙ Intelligent interface management

- ✱ 229 x 204 x 76 mm
- ✱ Wall mounted or DIN rail TS35
- ✱ 10/100 Mbit Ethernet, USB-Device, RS232 (SUB-D9), RS232C (Klemme), RS485, Repeater (M-Bus IN)
- ✱ integrated 110 ... 250V power supply



M-Bus Level Converter

Art.No.: DR003/DR004/DR005/DR006

- ⊙ RS232C Interface, 250 Slaves (DR003)
- ⊙ RS232C Interface, 120 Slaves (DR004)
- ⊙ RS485 Interface, 250 Slaves (DR005)
- ⊙ RS485 Interface, 120 Slaves (DR006)

- ✱ 85 x 200 x 240 mm
- ✱ Wall mounted
- ✱ RS485 or RS232C
- ✱ plug-in, wall mounted or DIN rail power supply (scope of delivery)



Repeater

Art.No.: DR007

- ⊙ M-Bus repeater for 250 slaves
- ⊙ Increases the number of possible slaves by 250
- ⊙ Increases the M-Bus extension (cable)

- ✱ 85 x 200 x 240 mm
- ✱ Wall mounted
- ✱ plug-in, wall mounted or DIN rail power supply (scope of delivery)



Mikro-Master

Art.No.: MR003 USB

- ⊙ Portable M-Bus level converter for 10 slaves
- ⊙ Power supply by laptop
- ⊙ USB interface

- ✱ 30 x 54 x 110 mm
 - ✱ RS232C or USB interface
 - ✱ Power supply by laptop
- Delivery contains:
- ✱ USB cable
 - ✱ Device driver for Windows



W60 Level Converter

Art.No.: MR004W

- ⊙ M-Bus level converter for 60 slaves
- ⊙ RS232C and RS485 interface
- ⊙ Integrated power supply

- ✱ 71 x 165 x 175 mm
- ✱ Wall mounted
- ✱ RS232C
- ✱ external modem
- ✱ integrated 230V or 110V power supply



PW60

Art.No.: MR004C

- ⊙ M-Bus level converter for 60 slaves
- ⊙ RS232C and RS485 interface
- ⊙ IR-opto-interface

- ✱ 78 x 70 x 118 mm
- ✱ Mounted on DIN rail TS35
- ✱ RS232C, RS485 and IR-opto-interface
- ✱ external power supply 12 .. 24 V (not in scope of delivery)



PW20

Art.No.: MR006 / MR006IR

- ⊙ M-Bus level converter for 20 slaves
- ⊙ RS232C interface
- ⊙ additional IR-opto-interface at the MR006IR

- ✱ 78 x 55 x 118 mm
- ✱ Mounted on DIN rail TS35
- ✱ RS232C or RS232C and additional IR-opto-interface
- ✱ external power supply 12 .. 24 V (not in scope of delivery)



PW3

Art.No.: MR005 / MR005IR

- ⊙ M-Bus level converter for 3 slaves
- ⊙ RS232C interface
- ⊙ additional IR-opto-interface at the MR005IR

- ✱ 78 x 55 x 118 mm
- ✱ Mounted on DIN rail TS35
- ✱ RS232C or RS232C and additional IR-opto-interface
- ✱ external power supply 12 .. 24 V (not in scope of delivery)